

Wall Mounted Heat Pump System

Location: _____
 Engineer: _____
 Submitted to: _____
 Submitted by: _____
 Reference: _____

Approval: _____
 Date: _____
 Construction: _____
 Unit #: _____
 Drawing #: _____

Indoor unit code 22022011016401
Model B-VMH30SG-1
 Indoor unit model MSEPD-30HRFN1-MS8W

Certified
 AHRI 
 UL 



SYSTEM PERFORMANCE DATA

Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V, 1Ph, 60Hz
Voltage Range	(V)	187-253
Room temperature		
Indoor(cooling)	(Deg. °F)	16~32
	(Deg. °C)	60~90
Indoor(heating)	(Deg. °F)	0~30
	(Deg. °C)	32~86

INDOOR UNIT DATA

Indoor fan motor		
Model		ZKFP-58-8-1-6
Qty		1.00
Input	(W)	58.00
Output	(W)	58.00
RLA	(A)	0.50
Speed(Hi/Mi/Lo)	(r/min)	1050/880/630
Air flow & Noise level		
Indoor air flow (Hi/Med/Lo) (No duct)	(CFM)	843.42/646.85/505.59/382.57
Indoor noise level (Hi/Med/Lo)	[dB(A)]	46/40.5/33
Indoor unit		
Dimension (WxDxH)	(inch)	44.88x10.82x14.57
	(mm)	1140x275x370
Packing(WxDxH)	(inch)	48.42x17.91x13.98
	(mm)	1230x455x355
Net/Gross weight	(lbs.)	43.65/54.89
	(kg)	19.8/24.9

Indoor unit dimension

